according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 **Print date:** 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

PUR-O-STOP SL B-Komponente

UFI:

4XDA-38WE-Y0RE-TC87

1.2. Relevant identified uses of the substance or mixture and uses advised against No data available

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

TPH Bausysteme GmbH

Nordportbogen 8 22848 Norderstedt

Germany

Telephone: +49 40 52 90 66 78-0
Telefax: +49 40 52 90 66 78-78
E-mail: info@tph-bausysteme.com
Website: www.tph-bausysteme.com

E-mail (competent person): sdb-info@tph-bausysteme.com

1.4. Emergency telephone number

24h: International access phone number: +1-813-248-0585 /// United States, Canada, Puerto Rico, U.S. Virgin Islands: 1-800-255-3924 (Contract No. MIS7249185) ///

Australia: 1-300-954-583 /// Brazil: 0-800-591-6042 /// China: 400-120-0751 /// India:

000-800-100-4086 /// Mexico: 800-099-0731

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	Calculation method.
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	Calculation method.
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	Calculation method.
Acute toxicity (inhalative) (Acute Tox. 4)	H332: Harmful if inhaled.	Calculation method.
Respiratory or skin sensitisation (Resp. Sens. 1)	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Calculation method.
STOT-single exposure (STOT SE 3)	H335: May cause respiratory irritation.	Calculation method.
Carcinogenicity (Carc. 2)	H351: Suspected of causing cancer.	Calculation method.
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure.	Calculation method.

Additional information:

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 **Print date:** 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:





GHS07

GHS08

Exclamation mark

Health hazard

Signal word: Danger

Hazard components for labelling:

Diphenylmethandiisocyanat, Isomere und Homologe

<u> </u>	- the second sec	
Hazard statements for health hazards		
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	

Supplemental hazard information	
EUH208	Contains Diphenylmethandiisocyanat, Isomere und Homologe, 4,4'-methylenediphenyl
	diisocyanate. May produce an allergic reaction.

Precautionary statements Prevention		
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P280 Wear protective gloves/protective clothing/eye protection/face protection.		

Precautionary statements Response		
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.	
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor/- if you feel unwell.	

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

idzardous ingredients / ridzardous impurities / Stabinsers.		
Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 9016-87-9	Diphenylmethandiisocyanat, Isomere und Homologe Acute Tox. 4 (H332), Carc. 2 (H351), Eye Irrit. 2 (H319), Resp. Sens. 1 (H334), STOT RE 2 (H373), STOT SE 3 (H335), Skin Irrit. 2 (H315), Skin Sens. 1 (H317) Danger	60 - 100 weight-%

Full text of H- and EUH-phrases: see section 16.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 Print date: 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended. Warning First aider: Pay attention to self-protection!

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician. Get medical advice/ attention. If breathing is irregular or stopped, administer artificial respiration. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. Get immediate medical advice/attention. Get medical advice/attention if you feel unwell.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Following ingestion:

Rinse mouth. Let water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell.

Self-protection of the first aider:

Use personal protection equipment. No direct artificial respiration to be given by first aider. First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Skin corrosion/irritation Allergic reactions Serious eye damage/eye irritation Asthmatic complaints Respiratory complaints Irritation to respiratory tract

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media:

Water

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

In case of fire: Gases/vapours, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 **Print date:** 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8).

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep/Store only in original container.

Hints on storage assembly:

Protect from moisture.

Storage class (TRGS 510, Germany): 10 - Combustible liquids that cannot be assigned to any of the above storage classes

7.3. Specific end use(s)

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 **Print date:** 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
Québec (CA)	Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9	① 0.005 ppm (0.051 mg/m³) ⑤ (4,4'-Methylenediphenyl diisocyanate - CAS 101-68-8)
NIOSH (US)	Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9	① 0.005 ppm (0.05 mg/m³) ③ 0.02 ppm (0.2 mg/m³) ⑤ (4,4'-Methylenediphenyl diisocyanate - CAS 101-68-8)
Alberta (CA)	Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9	① 0.005 ppm (0.07 mg/m³)
SI	Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9	 0.05 mg/m³ 0.05 mg/m³ (als MDI berechnet), (frakcija ki jo je mogoče vdihniti, računati je treba z možnostjo prodiranja skozi kožo) K, Y
TRGS 900 (DE)	Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9	① 0.05 mg/m³ ② 0.05 mg/m³ ③ 0.1 mg/m³ ⑤ (als MDI berechnet), (einatembare Fraktion), kann über die Haut aufgenommen werden DFG, H, Sah, Y, 12

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

No data available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection EN 166

Skin protection:

Tested protective gloves must be worn EN ISO 374 Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

Filtering device with filter or ventilator filtering device of type: A

8.2.3. Environmental exposure controls

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 **Print date:** 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: dark brown

Odour: earthy

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
рН	not determined		
Melting point	not determined		
Freezing point	not determined		
Initial boiling point and boiling range	245 °C		
Decomposition temperature	not determined		
Flash point	230 °C		① CC
Evaporation rate	not determined		
Auto-ignition temperature	not determined		
Upper/lower flammability or explosive limits	not determined		
Vapour pressure	not determined		
Vapour density	not determined		
Density	1.23 g/cm³	25 °C	① EN ISO 2811-1
Relative density	not determined		
Bulk density	not determined		
Water solubility	not determined		
Partition coefficient: n-octanol/water	not determined		
Dynamic viscosity	240 mPa* s	23 °C	① DIN EN ISO 2555
Kinematic viscosity	not determined		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Acids Water Alcohols Alkali (lye)

10.6. Hazardous decomposition products

Hydrocarbons Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid) Carbon monoxide Carbon dioxide (CO2)

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 **Print date:** 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9

LD₅₀ oral: >10,000 mg/kg (Rat) OECD 401

LD₅₀ dermal: >9,400 mg/kg (Rabbit) OECD 402

LC₅₀ Acute inhalation toxicity (vapour): 0.493 mg/L 4 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Harmful if inhaled.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Contains Diphenylmethandiisocyanat, Isomere und Homologe, 4,4'-methylenediphenyl diisocyanate. May produce an allergic reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Suspected of causing cancer.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9

LC₅₀: >1,000 mg/L 4 d (fish, Danio rerio (zebrafish)) OECD 203

EC₅₀: >1,000 mg/L (Daphnia magna (Big water flea)) OECD 202 24h

EC₅₀: >1,640 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus) OECD 201

EC₅₀: >100 mg/L (Activated sludge) OECD 209 3h

12.2. Persistence and degradability

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 Print date: 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

12.3. Bioaccumulative potential

Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9 **Bioconcentration factor (BCF): 200**

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Diphenylmethandiisocyanat, Isomere und Homologe CAS No.: 9016-87-9 Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Waste code product

08 05 01 *	Waste isocyanates
16 03 05 *	organic wastes containing hazardous substances

^{*:} Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number		
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.2. UN proper ship	ping name	·	
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport haza	rd class(es)		
not relevant	not relevant	not relevant	not relevant
14.4. Packing group			
not relevant	not relevant	not relevant	not relevant
14.5. Environmental	hazards		
not relevant	not relevant	not relevant	not relevant
14.6. Special precau	tions for user		
not relevant	not relevant	not relevant	not relevant

14.7. Maritime transport in bulk according to IMO instruments

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 **Print date:** 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

As from 24 August 2023 adequate training is required before industrial or professional use.

15.1.2. National regulations

[DE] National regulations

Water hazard class

WGK:

1 - schwach wassergefährdend

Other regulations, restrictions and prohibition regulations

Arbeitsmedizinische Grundsätze G27: "Isocyanate"

ZH 1/34 "Merkblatt: Polyurethan-Herstellung/Isocyanate (M 044)" ZH 1/129 "Merkblatt: Reizende Stoffe/Ätzende Stoffe (M 004)"

[DK] National regulations

Other regulations, restrictions and prohibition regulations

MAL-kode (Denmark): 00-5

15.2. Chemical Safety Assessment

No data available

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	Calculation method.
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	Calculation method.
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	Calculation method.
Acute toxicity (inhalative) (Acute Tox. 4)	H332: Harmful if inhaled.	Calculation method.
Respiratory or skin sensitisation (Resp. Sens. 1)	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Calculation method.
STOT-single exposure (STOT SE 3)	H335: May cause respiratory irritation.	Calculation method.
Carcinogenicity (Carc. 2)	H351: Suspected of causing cancer.	Calculation method.
STOT-repeated exposure (STOT RE 2)	H373: May cause damage to organs through prolonged or repeated exposure.	Calculation method.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 1 Nov 2022 **Print date:** 1 Nov 2022

Version: 2.4



PUR-O-STOP SL B-Komponente

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	Hazard statements	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	

16.6. Training advice

No data available

16.7. Additional information