

AKKUINJEKTOR

Properties:

The *AKKUINJEKTOR* is a small, light, electrically-driven 1-component injection pump for processing polyurethane and epoxy resins in addition to 1-component foams.

Due to its high transport pressure, the *AKKUINJEKTOR* is a fully-usable injection device for both minor and medium injection work.

The *AKKUINJEKTOR* is suitable for crack injection, area injection and horizontal barriers in concrete and brickwork.

Technical Data:

Container contents	:	1000 ml
Container length	:	51 cm
Working pressure	:	0 - 400 bar
Maximum flow rate	:	100 l/min
Dimensions	:	width 19 x depth 8 x height 29 cm
Weight	:	approx. 3.2 kg (with empty container)
Battery power	:	approx. 3 l injection product approx. 25 packer
Charging time of the battery	:	approx. 1 h
Length of high-pressure hose	:	0.7 m
Compression head	:	Coupling and pressure gauge

Processing:

For information on using the pump refer to the operation instructions of *AKKUINJEKTOR*.

Safety information:

Wear protective gloves, protective clothing and eye or face protection during injection work.

Before operation start-up the injection machine it is necessary to inform about the safety instructions. For further information please refer to the operation instructions.

Packaging:

Injection pump (ready-to-use)
inclusive two batteries and battery charger



Legal notice:

The correct and thus successful application of our products is not subject to our control. A guarantee can be issued for the quality of our products within the framework of our sales and supply conditions, however not for successful processing. All data and specifications in this specification sheet are based on the present state of the art and the right to changes and adaptations for the sake of development remains explicitly reserved. The consumption specifications designated by us can be only average empirical values, where deviations are possible on an individual basis and therefore cannot be excluded by us.

TPH Bausysteme GmbH
Nordportbogen 8
D-22848 Norderstedt

Tel.: +49 (0)40 / 52 90 66 78-0
Fax: +49 (0)40 / 52 90 66 78-78
e-mail info@tph-bausysteme.com
Web www.tph-bausysteme.com

